

## LISTING OF THE CLAIMS

1. (previously presented) An apparatus comprising:  
a first display screen configured for movement between a first position and a second position, wherein the first display screen at least partially covers a control switch and/or a second display screen when the first display screen is in the second position;  
and  
a control device configured to offer functionality of the control switch and/or display information from the second display screen on the first display screen when the first display screen is in the second position.
2. (previously presented) The apparatus according to claim 1, wherein the control device displays on the first display screen an image that has an appearance identical to or that resembles the appearance of the control switch or information from said second display screen.
3. (previously presented) The apparatus according to claim 1, wherein said control device displays an image on said first display screen that changes the surface dimensions of said control switch and information from said second display screen.
4. (previously presented) The apparatus according to claim 1, further comprising:  
a position-detection device which detects the position of said first display screen,  
wherein said control device offers functionality of the control switch and/or displays

information from the second display screen on the first display screen based on the position detected by the position-detection device.

5. (previously presented) The apparatus according to claim 1, further comprising:  
a switch-display-instruction-receiving device which receives a switch-display instruction from a user for switching a display on the first display screen; wherein said control device offers functionality of the control switch and/or displays information from the second display screen on the first display screen based on the instruction received by the switch-display-instruction-receiving device.

6. (previously presented) The apparatus of according to claim 1, further comprising: a movement-control device which controls the movement of said first display screen.

7. (previously presented) The apparatus according to claim 1, wherein said first display screen is associated with a panel member that is a storage-type panel member.

8. (previously presented) The apparatus according to claim 1, wherein said first display screen is associated with a panel member is a rotation-type panel member.

9. (previously presented) A method comprising:

moving a first display screen from a first position to a second position, wherein the first display screen at least partially covers a control switch and/or a second display screen when the first display screen is in the second position; and

offering functionality of the control switch and/or displaying information from the second display screen on the first display screen when the first display screen is in the second position.

10. (previously presented) A recording medium readable by a computer, tangibly embodying a program executable by the computer to perform a method, the method comprising:

activating a movement control device to move a first display screen from a first position to a second position, wherein the first display screen at least partially covers a control switch and/or a second display screen when the first display screen is in the second position; and

offering functionality of the control switch and/or displaying information from the second display screen on the first display screen when the first display screen is in the second position.